

Olympic FLG Series



FEATURES & OPTIONS

Door Preparation

Cross Bore: 2-1/8", Edge: 1"

Latch Backset

Exterior: 2-3/8" deadlatch standard Interior: 2-3/8" plainlatch standard UL Latch available for 20mins fire rating (other options available)

Faceplate

1" x 2-1/4" round corner standard (other options available)

Rolf

1/2" throw

Door Thickness

Fit 1-3/8" to 1-3/4" standard (extension kit available for 1-3/4" to 2-1/4" door)

Cylinder

5-pin KW keyway solid brass cylinder standard 5-pin SC "C" keyway available

Strike Plate

2-1/4" x 1-3/4" round corner full lip standard (other options available)

Handing

Non-Handed

Material

Zinc die-cast lever

ANSI/BHMA

A 156.2 Grade 3

FINISHES

(other finishes available upon request with lead-time)

- □ US3 605 Polished Brass
- ☐ US5 609 Antique Brass
- □ US15 619 Satin Nickel
- □ US26 625 Polished Chrome
- □ US26D 626 Satin Chrome
- ☐ US19 622 Matte Black

FUNCTIONS

Entry - F109 (FLG00)

Both lever locked or unlocked by key outside or turn-piece inside.

Privacy - F76 (FLG01)

Both levers locked or unlocked by turn-piece inside. Outside lever unlocked by coin or screwdriver.

Passage - F75 (FLG03)

Both levers always free.

Half Dummy (FLG04)

For doors where only pull is required.

Entry w/ ADA - F109 (FLG07C)

Outside lever locked or unlocked by key. Inside lever locked by push-button and always free with quick release function. No unlocking required for panic exit.

Privacy w/ ADA - F76 (FLG08C)

Outside lever lock or unlocked by coin or screwdriver. Inside lever locked by push-button and always free with quick release function. No unlocking required for panic exit.

Storeroom - F86 (FLG05)

Outside lever always fixed and unlocked by key only. Inside lever always free.

WARRANTY

- Lifetime mechanical warranty
- Five years finish warranty

CODE COMPLIANCE

Meets ADA Requirements

- Entry w/ ADA
- Privacy w/ ADA



