

Removable Mullion

For Exit Devices

FEATURES & OPTIONS

Mullion Tube

2" wide x 3" deep, with wall thickness of 1/8", 11 Gauge steel tube

Mullion Size

7' or 8', maybe field cut to fit proper size

Top Bracket

Base Size: 3-1/2" wide x 3-1/8" deep, Steel

Rim Cylinder

6-pin SC "C" keyway solid brass cylinder standard

Also available in: 5-pin KW keyway, 6 & 7-pin small format I/C Core, Best A2 keyway

Shims

1/2" and 5/8" shims included

Strikes

Non-Fire Rated: Standard Rim Strikes, not included

Fire Rated: Mullion Strikes & Strike Hooks, sold separately

Fasteners

2 Flat Head Machine Screws, #5/16"-18 x 1-1/2", plated steel

4 Flat Head Machine Screws, #5/16"-18 x 5/8", plated steel

4 Flat Head Machine Screws, #5/16"-18 x 1-1/4", plated steel

4 Expansion Anchors, 5/8" dia. X 7/8" long, nonferrous alloy

FINISH AVAILABILITY

- Gray baked powder coating (USP)

CODE COMPLIANCE



- UL10C positive pressure Rated
- UL 10B Negative Pressure Rated
- UL Listed for up to 3 hours
With Fire Rated Removable Mullion

WARRANTY

- One-Year Mechanical Warranty

