

# Keyed Removable Mullion

## *For Exit Devices*

### FEATURES & OPTIONS

#### Mullion Tube

2" wide x 3" deep, with wall thickness of 1/8", 11 Gauge steel tube

#### Mullion Size

7' or 8', maybe field cut to fit proper size

#### Top Bracket

Base Size: 3-1/2" wide x 3-1/8" deep, Steel

#### Rim Cylinder

6-pin SC "C" keyway solid brass cylinder standard

Also available in: 5-pin KW keyway, 6 & 7-pin small format I/C Core, Best A2 keyway

#### Shims

1/2" and 5/8" shims included

#### Strikes

Non-Fire Rated: Standard Rim Strikes, not included

Fire Rated: Mullion Strikes & Strike Hooks, sold separately

#### Fasteners

2 Flat Head Machine Screws, #5/16"-18 x 1-1/2", plated steel

4 Flat Head Machine Screws, #5/16"-18 x 5/8", plated steel

4 Flat Head Machine Screws, #5/16"-18 x 1-1/4", plated steel

4 Expansion Anchors, 5/8" dia. X 7/8" long, nonferrous alloy

### FINISH AVAILABILITY

- Gray baked powder coating (USP)

### CODE COMPLIANCE



- UL10C positive pressure Rated
- UL 10B Negative Pressure Rated
- UL Listed for up to 3 hours  
With Fire Rated Removable Mullion

### WARRANTY

- One-Year Mechanical Warranty

