

E910E

Rim Type w/ ELR



FEATURES

Voltage

24VDC @ 700 mA activation, 200 mA continuous

Door Width

For all doors up to 36" or 48" wide

Stile

2-5/8" minimum for single doors and standard 5/8" stop

Material

Cover: Stainless steel, zinc

Cover Tube: Aluminum

End Cap: Zinc

Strike

Stainless steel with plated rollers

Latch Bolts

3/4" throw, Pullman type with automatic dead-latching,

Stainless steel

Mounting

Furnished standard with wood, machine screws and thru-bolts

Backset

2-3/4" standard

Handing

Non-handed

Projection

3" maximum projection, 2-5/8" when depressed

Operation

Momentary or maintained latch bolt and push pad retraction, with simultaneous dogging. Automatic re-triggering of latch retraction.

OPTIONS

- REX – Request to Exit
- LBM – Latch Bolt Monitoring
- REXLBM – Request to Exit + Latch Bolt Monitoring

FINISHES

- US28 – 689 – Aluminum (Painted)
- US20 – 690 – Dark Bronze (Painted)
- US32D – 630 – Stainless Steel
- 313 - 622 - Black

WARRANTY

Life-Time mechanical warranty

One year electrical warranty

Five years finish warranty

CODE COMPLIANCE

ANSI A156.3, Grade 1

UL listed for Panic and UL10C, UBC 7-2-1997 code

AVAILABLE TRIMS



E9100
Escutcheon
Lever Trim

