

## GC5900 Series



### FEATURES & OPTIONS

- UL Listed (UL 10C)
- Universal application and non-handed installation (regular and parallel bracket included)
- Multi-size strength, power adjustable for size 1 thru 6 (factory preset size 3)
- Hardened steel rack and pinion mechanism
- Adjustable back check standard
- Fixing for both metal and timber doors
- Adjustable closing and latching speed
- Optional delay action
- Door weight range from 44 ~ 265 lbs
- Stable hydraulic fluid capable of withstanding temperature ranges of 105 degrees F. to -25 degrees F.
- Application: Maximum versatility door closer designed to be used for variety of both commercial and institutional application

### PACKAGE INCLUDES

- Parallel bracket
- Wood screws and machine screws
- Full plastic cover
- Sex bolts and Thru bolts

### FINISHES

- Aluminum (painted)
- Dark Brown (painted)
- Matte Black (painted)

### WARRANTY

- 25 years mechanical warranty
- Five years finish warranty



### CODE COMPLIANCE

- ANSI A156.4 Grade 1
- UL10C and UBC 7.2 for positive pressure
- Meets ADA barrier-free accessibility

### SPECIFICATIONS

**Closer:** Closers shall be by Pamex model # GC5900, full rack and pinion type with cast aluminum alloy body. All closers shall be provided with non-critical valves adjustment to independently regulate the sweep, latch and back-check. Closer shall have full spring adjustment from size 1 to 6 for barrier free (BF).

### APPLICATION

Maximum versatility door closer designed to be used for variety of both commercial and institutional application except for room or hallway that might be affected by high wind load or air pressure difference.

