VALENCIA

PLK Series



FEATURES & OPTIONS

Door Preparation

Cross Bore: 2-1/8", Edge: 1"

Latch Backset

Exterior: Adjustable deadlatch standard Interior: Adjustable plainlatch standard (other options available)

Faceplate

1" x 2-1/4" round corner standard (other options available)

Bolt

1/2" throw

Door Thickness

Fit 1-3/8" to 1-3/4" standard

Cylinder

5-pin KW keyway solid brass cylinder standard

Strike Plate

2-1/4" x 1-3/4" round corner full lip standard (other options available)

Handing

Specify right or left handed door. Reversible levers available

Material

Zinc die-cast lever

ANSI/BHMA

A 156.2 Grade 3

FINISHES

(other finishes available upon request with lead-time)

- □ US3 605 Polished Brass
- ☐ US12P 716 Dark Bronze
- □ US15 619 Satin Nickel

WARRANTY

- □ 25-year mechanical warranty
- ☐ Five years finish warranty

FUNCTIONS

Entry - F109 (PLK00)

Both lever locked or unlocked by key outside or turn-piece inside.

Passage - F75 (PLK03)

Both levers always free.

Privacy - F76 (PLK01)

Both levers locked or unlocked by turn-piece inside. Outside lever unlocked by coin or screwdriver.

Half Dummy (PLK04)

For doors where only pull is required.

