

# Removable Cylinder Deadbolt *FD8 Series*



### FEATURES & OPTIONS

#### Door Preparation

Cross Bore: 2-1/8", Edge: 1"

#### Latch Backset

2-3/8" deadbolt standard  
(other options available)

#### Faceplate

1" x 2-1/4" round corner standard  
(other options available)

#### Bolt

1" throw

#### Door Thickness

Fit 1-3/8" to 1-3/4" standard  
(extension kit available for 1-3/4" to 2-1/4" door)

#### Cylinder

Removable cylinder for easy replacement  
5-pin KW keyway zinc die-cast housing standard  
5 and 6-pin SC "C" keyway available

#### Strike Plate

2-3/4" x 1-1/8" square corner standard  
(other options available)

#### Handing

Non-Handed

#### ANSI/BHMA

A 156.5 Grade 2

### FINISHES

(other finishes available upon request with lead-time)

- US32D - 630 - Satin Stainless Steel
- US19 - 622 - Mate Black

### WARRANTY

Lifetime mechanical warranty

Five years finish warranty



ADA



### CODE COMPLIANCE

Meets ANSI/BHMA A156.36,

Series 4000, Grade 2

Meets ADA Requirements

UL 3-Hour Fire Rated (when  
equipped with UL listed latch)

### SPECIFICATIONS

**Lockset:** Grade 2 tubular removable cylinder deadbolt lock shall be by **PAMEX** model # **FD8 Series**. Deadbolt shall be non-handed, reversible with removable cylinder for easy replacement. The bolt shall be made with hardened steel insert for saw resistant and have 1" projection.

### FUNCTIONS

#### Single Cylinder

Bolt is operated by key from outside and turn-piece inside. Cylinder is removable by control key for easy replacement.

#### Single Cylinder With UL Listed Latch

UL listed bolt is operated by key from outside and turn-piece inside. Cylinder is removable by control key for easy replacement.

