Pamex Locks

Alhambra FSL Series

FEATURES & OPTIONS

Door Prep.

Cross Bore: 2-1/8", Edge: 1" Center to Center: 5-1/2"

Interior Trim FTF-Baron knob interior trim (other options available)

Latch Backset

Deadbolt: 2-3/8" deadbolt standard Handle: 2-3/8" plainlatch standard (other options available)

Faceplate

1" x 2-1/4" round corner standard (other options available)

Bolt Deadbolt: 1" throw Lever: 1/2" throw

Door Thickness Fit 1-3/8" to 1-3/4" standard (extension kit available for 1-3/4" to 2-1/4" door)

Cylinder

5-pin KW keyway solid brass cylinder standard 5-pin SC "C" keyway available

Strike Plate

Deadbolt: 2-1/4" x 1-3/4" full lip round corner standard Handle: 2-1/4" x 1-3/4" full lip round corner standard (other options available)

Handing Specify handing when order lever interior trim

ANSI/BHMA A 156.2 Grade 2

FINISHES

(other finishes available upon request with lead-time)

□ USL03 – 505 – Lifetime Polished Brass

- □ US15 619 Satin Nickel
- □ US11P Venetian Bronze

WARRANTY

- Lifetime mechanical warranty
- Five years finish warranty

FUNCTIONS

Single Cylinder

Deadbolt operated by key outside and turn-piece inside. Latchbolt operated by thumb-piece outside and knob or lever inside.

Double Cylinder

Deadbolt operated by key on both sides. Latchbolt operated by thumb-piece outside and knob or lever inside.

Dummy

Handle and knob or lever act as pull only. No operation.





