



Deadbolt KT-D7 Series

ELECTRICAL

Technologies

Bluetooth

Frequency

13.56MHz RFID

Read Range

1 cm (ISO Card); MIFARE: S70 EV1

Power Supply

4 AA Batteries (average 1 year)

Operating Temperature

-30 to 120F

Event Log

6,000 events

MECHANICAL

Door Preparation

Cross Bore: 2-1/8", Edge: 1-1/8"

Latch Backset

Adjustable UL deadbolt standard
(other options available)

Faceplate

1-1/8" x 2-1/4" square corner standard
(other options available)

Bolt

1" throw

Door Thickness

Fit 1-3/8" to 1-3/4" standard

Cylinder

5-pin KW keyway standard
Also available in 6-pin SC keyway

Strike Plate

2-3/4" x 1-1/8" square corner strike standard with
reinforced plate and 3" wooden screws
(other options available)

Handing

Non-Handed

FINISHES

(other finishes available upon request with lead-time)

- US10B – 613 – Oil Rubbed Bronze
- US15 – 619 – Satin Nickel

WARRANTY

- Lifetime mechanical warranty
- One year electrical warranty
- Five years finish warranty

CODE COMPLIANCE

- ANSI/BHMA Grade 2 certified
- ANSI 117.1 for ADA
- UL10C and S104 (90 minutes)

