

Mortise Locks

MS Series Deadbolt



FEATURES & OPTIONS

Door Thickness

1-3/4" standard; for doors over 1-3/4" specify door thickness

Backset

2-3/4" only

Lock Hand

Lock bodies are easily field reversible

Lock Case

Heavy duty wrought steel, zinc dichromate plated

Armor Faceplate

Stainless steel; 5-5/8"x1-7/32"; ANSI standard A115.1

Deadbolt

1" throw, hardened stainless steel

Auxiliary Latch

Stainless steel, non-handed

Strike

Stainless steel; Square Corner Strike with dust box; ANSI standard A115.1

Cylinder

6-pin SC "C" keyway solid brass cylinder standard

Also available in:

5-pin SC keyway

5-pin KW keyway

6 or 7-pin SFIC

FINISHES

(other finishes available upon request with leadtime)

US26D – 626 – Satin Chrome

CODE COMPLIANCE

- Meets ANSI/BHMA A156.13, Series 4000, Grade 1
- Meets ADA Requirements
- UL 3-Hour Fire Rated

FUNCTIONS

- 17 – Cylinder and Thumbturn (F17)
- 18 – Cylinder Lock (F18)
- 16 – Double Cylinder (F16)

WARRANTY

- Lifetime mechanical warranty
- Five years finish warranty

